





specifications: Isuzu 'Grafter' N35.125(T) Utilitruck

3.5T GVW / EURO 6d (WLTP) 4x2 rigid twin rear wheels



Axle weights (kg)			
UK maximum Vehicle Weights (kg)		GVW	3500
		GTW*	7000
UK Axle design weights (kg)		Front	2100
		Rear	2435
Weights (kg) PROVISIONAL			
Cab type			day
Wheelbase		WB	3360
Vehicle Mass Unladen		Front	1484
		Rear	1016
Total			2500
GVW			3500
Payload Allowance			1000
Max. Permissible Trailer Weight*			3500
Dimensions (mm)			
Body Length		External Body Length	3350
		Internal Body Length	3250
Body Width	OVW	External Body Width	1950
-		Internal Body Width	1890
Full size toolpod with galvanised steel end frames		Toolpod Height	1460
Includes aluminium roller shutter with hasp & staple		Toolpod Length	2000
Internal single width shelf at half height		Toolpod Depth	800
Features			
Fully galvanised steel sub frames	Fully galvanised steel tipping gear		
Multistage direct lift under floor ram	Wander lead control complete with 'Body Up' warning light		
Dual tone audible warning buzzer	Electro hydraulic power pack with thermoplastic oil reservoir		
Hose burst safety valve	Rubber mou	lded body rests	
Heavy duty galvanised gantry with lower alloy infill and upper 'Isuzu' pressed infill	18mm alloy 'Tippadeck' heavy duty interlocking floor system		
Single 400mm high alloy mill finish drop side boards c/w recessed spring catches	400mm high alloy mill finish tailboard with 2-way hinge assembly and rubber stops		
Fully galvanised heavy duty removable corner posts	Heavy duty under floor tie points either side		
Half round thermoplastic mud wings	Integral body prop		
Safety decals and colour instruction manual	Front and rear marker lights		
Towbar with pin/ball hitch and seven pin electrics	400mm LED	beacon bar	

*Tachograph regulations may apply

 Unladen weights excludes driver, fuel and AdBlue[®], Includes spare wheel + carrier, Tolerance +/- 3%). Spare wheel and carrier 38kg. 2. The bodybuilder has ensured all legal requirements have been met. 3. Isuzu Truck (UK) Ltd. shall have no liability whatsoever should the information supplied have incorrect data, descriptions or illustrations.

N35.125(T) 6d (WLTP) Utilitruck Mechanical Specification (standard equipment)

POWER & TORQUE CHASSIS DETAILS CAB FEATURES Electrical Cab Exterior Engine Steering Make & model: RZ4E Isuzu turbo Type: 1 x 12V 595CCA 65Ah battery with Type: Hexapod, white (standard) or metallic Features: Rack and pinion with full integral intercooled DOHC 4 cylinder 12V/150A alternator. grey (option), all-steel. hydraulic power assistance. Tilt and diesel. Lean NOx trap. DPD telescopic steering column. Tyres/Wheels Features: Manual tilt to 45 deg. Tinted windscreen. & SCR Chrome radiator grille. Plastic resin Instruments 205/75 R16 radial Tyres: Bore x stroke: 80 x 94.4mm non-slip entry steps. 90 dea. openina Speedometer with odometer & trip. Features: 5.50J x 16, 5-stud Wheels: doors. Zinc galvanised frame structure. Capacity: Max Power: Rev counter. Fuel gauge. Engine coolant Steel reinforced composite front bumper. Spare: 1 x wheel and tyre. temperature. Multi-information display with fog and daytime running lamps. provides information on servicing, Frame Two halogen head lamps with indicators. **.** emissions and fuel economy. AdBlue® Front mudguards with spray suppression. **120**PS 1898 Parallel ladder type channel section straight side level. DPD operation. Calendar. Clock. Type: Keyless door entry and immobiliser. Rear rails, riveted upper flange. under run bar protection (R58.03) 88 Switches & Electrical Axles Features: Combination stalk incorporating Front: Independent type. **Cab Interior** headlamps, indicators, fog lamp, Rear: Banio fully floating. washers and wipers. Auto lights. Steering at 3200rpm Features: Flame-resistant interior trim. Vinvl floor wheel horn. Headlamp levelling. matting. Pillar mounted entrance grab Suspension Engine quick warm-up. Central locking. Transmission handles both sides. Driver & passenger Cigarette lighter. DPD, EVSC and ASR Double wishbone and transverse parallel leaf SRS airbags. Make & model: Isuzu 6 speed manual synchromesh Front: control. Hazard warning lights. suspension with hydraulic shock absorbers. MVC6W overdrive. Kenwood DAB radio with Bluetooth (Sat Semi-elliptical steel suspension with hydraulic Seats (cloth) Nav option available). Ratios: 1st - 4.942; 2nd - 2.686; 3rd - 1.527 Rear: shock absorbers. 4th - 1.000: 5th - 0.796: 6th - 0.634: Features: Driver's fully adjustable suspension seat Reverse - 4 597 **Brakes** with head restraint. Dual passenger seat with folding back. Driver and outer Warning/Indicator Lamps Rear Axle Ratio: 4.777:1 System: Vacuum servo assisted hydraulic dual line passenger retractable diagonal seat belts with ABS, EBD (electronic brake distribution), Features: Battery charge. Oil pressure. Low fuel. with pre-tensioner. Centre seat lap belt. Clutch EVSC (electronic vehicle stability control), Glow plug operation. High beam and Upholstery shade upgrade. ASR (anti slip regulation). indicators. Park brake warning. Fuel/ Type: 275mm diaphragm type with hydraulic actuation. water separator. Check engine. Engine Front: 293mm ventilated discs with asbestos free pads. - Contract (1997) over heat, EVSC, ABS, Front and rear fog Rear: 275mm ventilated discs with asbestos free pads. **Power & Torque** Vision lights. Seat belt warning and reminder. Park: Brake fluid level, SRS air bag, Brake Mechanical drum brake rear of transmission ---- Power ---- Torque Features: Large foldable mirrors. Interior rear vacuum loss. Cab tilt lock warning. Airbag view mirror on collapsible mounting. Fuel Tank pictogram. Driver and passenger sun visors. Deep er[kw] 70 AdBlue®: 320Nm at 1600rpm Capacity: cut side windows to reduce blind spots. 350 Electric windows with driver control ⁸ 60 300 and lock. **Tool Kit** 50 250 Features: Jack with a small selection of hand tools. 40 200 30 150 100 WARRANTY 10 LITDES LITRES 1000 2000 3000 Engine Speed (rpm) 4000 All chassis cabs come with a 3 year unlimited mileage warranty and roadside assistance as standard.

SAFETY & SECURITY

Complies with ECE-R29 cab strength standard.	
Central locking with remote keyless entry and immobiliser.	
ntegral towbar and rear under run bar.	
Red diagonal and lap belts.	
nte	

N35.125(T) 6d (WLTP) Utilitruck spec sheet: 14648

N35.125(T) 6d (WLTP) Utilitruck spec sheet: 05/2021

f y in 🕬

01707 282930 | www.isuzutruck.co.uk

For further information please contact vour local dealer or phone us direct:

Utilitruck bodies come with the bodybuilder's three year, 100,000 mile warranty. Terms and conditions apply.

Isuzu-backed Repair and Maintenance contracts available upon request.

